








Typ Bestell-Nr.	Bezeichnung	Schirmungsmaß		Passend für Kabel	Verpackungseinheit/ Gewicht (St./kg)
EMK 08 273171	IEC-Stecker	VHF: > 75 dB UHF: > 65 dB		LCD 89, 90, 95, 99, 111, 115	10 (100)/ 0,06
EMK 21 273120	IEC-Stecker	VHF: > 75 dB UHF: > 65 dB		LCD 89, 90, 95, 99, 111, 115	10 (100)/ 0,11
EMK 62 273123	IEC-Buchse	VHF: > 75 dB UHF: > 65 dB		LCD 89, 90, 95, 99, 111, 115	10 (100)/ 0,12

## IEC-Kupplungen

Typ Bestell-Nr.	Bezeichnung		Anschluss	Verpackungseinheit/ Gewicht (St./kg)
EMU 01 273247 	IEC-Kupplung		IEC (Sti) - IEC (Sti)	10 (100, 1000)/ 0,04
EMU 10 273275 	IEC-Kupplung		IEC (Bu) - IEC (Bu)	10 (100, 1000)/ 0,1

## Abschlusswiderstände

Typ Bestell-Nr.	Bezeichnung	Schirmungsmaß		Anschluss	Verpackungseinheit/ Gewicht (St./kg)
EMK 03 273169 	F-Abschlusswiderstand	> 120 dB (5-1000 MHz) > 105 dB (1000-2400 MHz)		F (Sti)	10 (100, 2000)/ 0,03
ERA 12 272822	Abschlusswiderstand	-		Klemmbar	10 (100, 1000)/ 0,01
ERA 14 272899	Abschlusswiderstand	-		Klemmbar, mit kapazitiver Trennung	10 (100, 1000)/ 0,01